

COMMERCIAL REVERSE OSMOSIS • COMPACT POINT-OF-USE

Noble RO 60

Our compact reverse osmosis system for sites that need premium water in tight spaces — sitting below Imperial and Majestic in size, yet delivering consistent performance for coffee bars, small kitchens and back-of-house installs where reliability matters.

COMPACT

MULTI-STAGE

SILENT

NOB 60



WHY SPECIFY IT

Quality you can taste and trust.

Reverse osmosis paired with carbon block pre-filtration removes taste-affecting compounds and protects the membrane — with an adjustable salinity regulator so you can dial in the final TDS to your recipe or equipment specification.



Compact footprint

Just 96 mm wide — built for tight back-of-house spaces where premium water is needed but room is limited.



Adjustable salinity regulator

Set the final TDS to your recipe or equipment spec — so espresso tastes balanced, steam equipment runs cleaner and glassware dries clear.



Silent, serviceable design

A silent external pump and ABS housing — wall-mounted or floor-standing, simple to service with routine filter changes.

60L/h

PURIFIED FLOW

220GPD

RO MEMBRANE

9.5kg

UNIT WEIGHT

96mm

FOOTPRINT WIDTH

TDS

adjustable salinity

Dial in the taste

An integrated salinity regulator lets you set the final TDS to your recipe or equipment specification — so espresso tastes balanced, steam equipment runs cleaner and glassware dries clear. Carbon block pre-filtration protects the membrane and removes taste-affecting compounds.



SPECIFICATIONS

Technical detail.

Model	NOB 60	Salinity regulator	Integrated
Order code	FLO NOBFLT60	Power supply	220 V AC · 50/60 Hz
Datasheet ref	SWC-NOB60-25-RO	Power consumption	115 W
Type	Reverse osmosis	Feed water pressure	0.5–5 bar
Purified water flow	60 L/h	Feed water temp.	5–35 °C
RO membrane	1 × 220 GPD	Feed water quality	Potable
Pump	Silent · external	Dimensions (W×D×H)	96 × 435 × 378 mm
Carbon block pre-filter	Yes	Weight / build	9.5 kg · ABS

Carbon block Pre-filter	RO membrane 220 GPD	Salinity Adjustable
		
Removes taste-affecting compounds and protects the membrane.	Reverse osmosis for consistent premium-quality water.	Regulator sets the final TDS to your recipe or equipment spec.

HOW IT WORKS

From mains to pure water.

01 Potable mains	02 Carbon block pre-filter	03 RO membrane	04 Salinity regulation	05 Purified output
---------------------	-------------------------------	-------------------	---------------------------	-----------------------

SCOPE OF SUPPLY

What we provide.

- ✓ Noble RO 60 system (NOB 60 · FLO NOBFLT60)
- ✓ 220 GPD reverse osmosis membrane
- ✓ Carbon block pre-filtration stage
- ✓ Integrated adjustable salinity regulator
- ✓ Silent external pump · wall-mount or floor-stand fittings
- ✓ Optional Comprehensive Maintenance plan

Where it fits best

Ideal for specialty coffee machines, steam and combi ovens, small ice makers and point-of-use drinking dispensers — especially where space is limited but water quality cannot be compromised.

[COMMERCIAL · BY QUOTE](#)[REQUEST A QUOTE](#)**Specify the Noble RO 60 for your site.**

British-engineered, European-manufactured. UK · Middle East · Europe.

+44 20 8050 2115

sales@sovereignwater.co.uk

124 City Road, London EC1V 2NX